

PI6HP, PI6HPZ, PI6AP, PI6APZ

FAST AND RELIABLE FOR FIELD SERVICE REPAIRS

Finn-Power P16 series crimping machines are compact, strong and reliable for any service crimping need.Their compact design allows efficient working and easy transport between any locations. PI6 machines are easy to use and they produce high quality crimping day after day.

CONTROL



AVAILABLE MODELS



HP

AP

DIE SET P16

Pno	Crimp. range	D	L
18212/10	10.0 - 12.0	10	55
18212/12	12.0 - 14.0	12	55
18212/14	14.0 - 16.0	14	55
18212/16	16.0 - 19.0	16	55
18212/19	19.0 - 23.0	19	55
18212/23	23.0 - 27.0	23	55
18212/27	27.0 - 31.0	27	65
18212/31	31.0 - 38.0	31	65

FEATURES

CRIMPIN

CRIMPIN

MAX OPEN MAX CRIM

MAX CRIM NUMBER C PUMP PUMP WEIGHT (K

WEIGHT (I

MEASURE

 With sta Crimpin increase 2) Theoretical with 10 mm cycle.

	P16HP - PORTABLE	P16HPZ - FLEXIBLE	P16AP - COMPACT	P16APZ - FLEXIBLE
S	Manually operated hydraulic crimping machine for repair workshops. Easy to use, lightweight and compact in size.	Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.	Suitable for workshops where compressed air is available. This lightweight machine can easily be carried by hand in need of relocation.	Machine is connected to pump with a flexible hydraulic hose that enables crimping in tight and difficult spaces.
	P16	P16	P16	P16
G RANGE (MM) ⁽¹	10-45	10-45	10-45	10 - 45
G RANGE (INCH) ⁽¹	0.39 - 1.77	0.39 - 1.77	0.39 - 1.77	0.39 - 1.77
ENING (MM)	+20	+20	+20	+20
MPING FORCE (KN)	955	955	955	955
MPING FORCE (TON.)	95	95	95	95
OF CRIMPS/HOUR ^{[2}			-	_
,	HAND PUMP	HAND PUMP	AIR PUMP	AIR PUMP
	HAND PUMP	HAND PUMP	AIR PUMP	AIR PUMP
(KG)	26	28	28	26
(LBS)	57	62	62	57
EMENTS				
standard dies. ing range can be	331 mm / 13.1"	331 mm / 13.1"	331 mm / 13.1"	241 mm / 9.5"
sed with special dies.				