





P20NMS

650 mm / 25.6"



P20NMS

675 mm / 26.6"



P32NMS

FINN-POWER P20NMS AND P32NMS CRIMPING MACHINES FOR SERVICE USE

P20NMS & P32NMS – ROBUST AND FAST

New Finn-Power P20NMS and P32NMS, strong, fast and reliable crimpers for any service crimping need. These models turn hydraulics off to conserve energy and to reduce workplace noise levels whenever the machine is idle.

OPTIONS P20NMS & P32NMS

- Tool base with quick-change tool
- Tool rack with quick-change tool
- Mechanical backstop device
- Foot pedal

DIE SET TABLE P20

Pno	Crimp. range	D	L
18013/10	10.0 - 12.0	10	55
18013/12	12.0 - 14.0	12	55
18013/14	14.0 - 16.0	14	55
18013/16	16.0 - 19.0	16	55
18013/19	19.0 - 23.0	19	55
18013/23	23.0 - 27.0	23	55
18013/27	27.0 - 31.0	27	70
18013/31	31.0 - 36.0	31	70
18013/36	36.0 - 41.0	36	75
18013/41	41.0 - 47.0	41	75
18013/47	47.0 - 54.0	47	85
18013/54	54.0 - 61.0	54	85

DIE SET TABLE P32

Pno	Crimp. range	D	L
18506/10	10.0 - 12.0	10	55
18506/12	12.0 - 14.0	12	55
18506/14	14.0 - 16.0	14	55
18506/16	16.0 - 19.0	16	55
18506/19	19.0 - 22.0	19	55
18506/22	22.0 - 26.0	22	70
18506/26	26.0 - 30.0	26	70
18506/30	30.0 - 34.0	30	70
18506/34	34.0 - 39.0	34	75
18506/39	39.0 - 45.0	39	75
18506/45	45.0 - 51.0	45	90
18506/51	51.0 - 57.0	51	90
18506/57	57.0 - 63.0	57	100
18506/63	63.0 - 69.0	63	110
18506/69	69.0 - 75.0	69	110
18506/74	74.0 - 80.0	74	110
18506/78	78.0 - 87.0	78	110

	P20NMS	P32NMS
Crimping range (mm) ¹⁾	10 - 61	10 - 87
Crimping range (inch) ¹⁾	0.39 - 2.40	0.39 - 3.42
Max. opening (mm)	+25	+33
Max. crimping force (kN)	1370	2000
Max. crimping force (tonnage)	137	200
Number of crimpings/hour ²⁾	258 / 1000 ³⁾	200 / 850 ³⁾
Motor (kW)	1.5 / 3 ³⁾	1.5 / 4
Motor (HP)	2.0 / 4 ³⁾	2.0 / 5.5
Weight (kg)	140	190
Weight (lbs)	309	419



<http://powerco.lillbacka.com/products/general-production>

1) With standard dies. Crimping range can be increased with special dies.

2) Theoretical with 10 mm cycle

3) 1-phase / 3-phase