

TRELLFLEX CHEM 10 PG



TRELLFLEX CHEM 10 PG

OIL & GAS

Applications

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste and all petroleum products with aromatic content up to 100%. For road and rail tanker equipment or fixed installations in the chemical industry.

Advantages

- Easy to handle due to hose flexibility (low bending radius).
- Usable at a wide range of temperatures.
- Capable of handling many different chemicals.

Technical description

fhspdfgenerator.spiraledesc polypropylene coated steel.

Inner tube: polypropylene film, null.

Reinforcement: polypropylene layers.

Cover: PVC coated fabric, grey, corrugated.

fhspdfgenerator.spiraleext: galvanized steel.

Temperature range: -30 °C to +80 °C.

Electrical properties: $\leq 1.0 \Omega/m$.

Standard/Approval

EN 13765 and ADR.

Couplings/Fittings

All types of swaged couplings:

- Guillemin (aluminium, gun-metal, stainless steel) ;
- thread swivel, male and female ;
- Cam action quick couplings (Kamlok type).

Fixed or swivel flange ISO PN10/16, PN20 (ASA150).

Complementary information

Fitted lengths are delivered on request with pressure test certificate.

Imperial size on request.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Length m	Article number	Stock or min. order m
50	62	10.0	40	0.9	180	1.97	30	30	5513236	•
65	78,5	10.0	40	0.9	200	2.82	30	30	5513237	30
80	95	10.0	40	0.9	280	3.3	30	30	5513238	•
100	118	10.0	40	0.9	400	3.96	30	30	5513239	•

• Upon availability.

* Tolerance on length: $\pm 1 \%$ (ISO 1307 Standard)

Branding

TRELLFLEX CHEM EN 13765:2015 DN 50-250 - NP 10 bar - +80°C - PP - 000000