



# TRELLFLEX CHEM 14 PG

## TRELLFLEX CHEM 14 PG

### OIL & GAS

#### Applications

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste and all petroleum products with aromatic content up to 100%. For road and rail tanker equipment or fixed installations in the chemical industry.

#### Advantages

- Easy to handle due to hose flexibility (low bending radius).
- Usable at a wide range of temperatures.
- Capable of handling many different chemicals.

#### Technical description

**fhspdfgenerator.spiraledesc** polypropylene coated steel.

**Inner tube:** polypropylene film, null.

**Reinforcement:** polypropylene layers.

**Cover:** PVC coated fabric, grey, corrugated.

**fhspdfgenerator.spiraleext:** galvanized steel.

**Temperature range:** -30 °C to +80 °C.

**Electrical properties:**  $\leq 2.5\Omega/m$  for ID<50mm,  
 $\leq 1.0\Omega/m$  for ID $\geq$ 50mm.

#### Standard/Approval

EN 13765 and ADR.

#### Couplings/Fittings

All types of swaged couplings:

- Guillemin (aluminium, gun-metal, stainless steel) ;
- thread swivel, male and female ;
- Cam action quick couplings (Kamlok type).

Fixed or swivel flange ISO PN10/16, PN20 (ASA150).

#### Complementary information

Fitted lengths are delivered on request with pressure test certificate.

Imperial size on request.

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Length m	Article number	Stock or min. order m
25	37	14.0	56	0.9	100	0.84	30	30	5513252	•
32	43	14.0	56	0.9	120	1.03	30	30	5513253	30
40	52	14.0	56	0.9	140	1.26	30	30	5513254	30
50	62	14.0	56	0.9	180	1.55	30	30	5513255	•
65	78,5	14.0	56	0.9	200	2.51	30	30	5513256	30
80	95	14.0	56	0.9	280	2.88	30	30	5513257	•
100	121	14.0	56	0.9	400	4.7	30	30	5513258	•
125	149	14.0	56	0.9	450	8.16	15	1	5603648	30
150	180	14.0	56	0.9	500	10.8	20	1	5603649	30
200	234	14.0	56	0.9	740	17.6	20	1	5603650	30
250	297	14.0	56	0.9	920	22.5	12	1	5603651	30

• Upon availability.

\* Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard)

#### Branding

TRELLFLEX CHEM - EN 13765 2000 - DN 150 - 3 - WP 24 bar - + 80°C - PP - 000000