

# TRELLFLEX OIL 10 GG



## TRELLFLEX OIL 10 GG

### OIL & GAS

#### Applications

Suction and discharge of light or heavy petroleum products and derivatives with aromatic content up to 100%.  
Road and rail equipment or fixed installations.

#### Advantages

- Both black and white oil can be carried.
- Low bending radius.

#### Technical description

**hspdfgenerator.spiraledesc**galvanized steel.

**Inner tube:** polypropylene film, null.

**Reinforcement:** polypropylene layers.

**Cover:** PVC coated fabric, black, corrugated.

**hspdfgenerator.spiraleext:** galvanized steel.

**Temperature range:** -30 °C to +80 °C.

**Electrical properties:**  $\leq 1.0\Omega/m$ .

#### Standard/Approval

EN 13765 and ADR.

#### Couplings/Fittings

All types of swaged couplings:

- Guillemin (aluminium, gun-metal, stainless steel) ;
- thread swivel, male and female ;
- Cam action quick couplings (Kamlok type).

Fixed or swivel flange ISO PN10/16, PN20 (ASA150).

#### Complementary information

Fitted lengths are delivered on request with pressure test certificate.

Imperial size on request.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Length m	Article number	Stock or min. order m
50	62	10.0	40	0.9	180	1.97	30	30	5513225	•
65	78,5	10.0	40	0.9	200	2.82	30	30	5513226	•
80	95	10.0	40	0.9	280	3.3	30	30	5513227	•
100	118	10.0	40	0.9	400	3.96	30	30	5513228	•

• Upon availability.

\* Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard)

#### Branding

TRELLFLEX OIL - EN 13765-2010 - DN - Type 2 - WP 10 bar - + 80°C - PP - 00/1111