

TRELLFLEX OIL 14 GG



TRELLFLEX OIL 14 GG

OIL & GAS

Applications

Suction and discharge of light or heavy petroleum products and derivatives with aromatic content up to 100%.
Road and rail equipment or fixed installations.

Advantages

- Both black and white oil can be carried.
- Low bending radius.

Technical description

fhspdfgenerator.spiraledesc galvanized steel.

Inner tube: polypropylene film, null.

Reinforcement: polypropylene layers.

Cover: PVC coated fabric, black, corrugated.

fhspdfgenerator.spiraleext: galvanized steel.

Temperature range: -30 °C to +80 °C.

Electrical properties: $\leq 2.5\Omega/m$ for DN<50mm,
 $\leq 1.0\Omega/m$ for DN \geq 50mm.

Standard/Approval

EN 13765 and TMD.

Couplings/Fittings

Guillemin: aluminium, gun-metal, stainless steel.

Knuckles thread swivel, male and female: aluminium or gun-metal.

Cam action quick couplings (Kamlok type).

Fixed or swivel ISO PN10/16, PN20 (ASA 150).

Complementary information

Fitted lengths are delivered on request with pressure test certificate.
Imperial size on request.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Length m	Article number	Stock or min. order m
25	37	14.0	56	0.9	100	0.84	30	30	5513229	30
32	43	14.0	56	0.9	120	1.03	30	30	5513230	30
40	52	14.0	56	0.9	140	1.26	30	30	5513231	30
50	62	14.0	56	0.9	180	1.55	30	30	5513232	30
65	78,5	14.0	56	0.9	200	2.51	30	30	5513233	30
80	95	14.0	56	0.9	280	2.88	30	30	5513234	•
100	121	14.0	56	0.9	400	4.7	30	30	5513235	•
125	149	14.0	56	0.9	450	8.16	15	1	5603644	30
150	180	14.0	56	0.9	500	10.8	20	1	5603645	30
200	234	14.0	56	0.9	740	17.6	20	1	5603646	30
250	297	14.0	56	0.9	920	22.5	12	1	5603647	30

• Upon availability.

* Tolerance on length: $\pm 1\%$ (ISO 1307 Standard)

Branding

TRELLFLEX OIL - EN 13765:2010 - DN - Type 3 - WP 14 bar - +80°C - PP - 00/0000