

# 4SH EVO – MSHA

## RUBBER HYDRAULIEKSLANG OVERTREFT 4SH NORMEN



### TECHNISCHE GEGEVENS BIJ 20°C

<b>Inwendig:</b>	(Bio-)oliebestendig synthetisch rubber
<b>Inlagen:</b>	4 staaldraadspiraal met hoge treksterkte
<b>Uitwendig:</b>	Minetuff cover, slijtvast en ozonbestendig, vuurbestendig
<b>Temperatuurbestendigheid continu:</b>	-40°C +120°C
<b>Omgevingstemperatuur:</b>	-40°C +80°C
<b>Rollengte:</b>	Variabel
<b>Normen:</b>	ISO18752
<b>Opdruk:</b>	Alfagomma Alfabiotech Minetuff Evolution
<b>Opmerkingen:</b>	Minetuff cover voor top slijtvastheid en ozonbestendigheid MSHA approved – vuurbestendige cover Bio-oliebestendig Extreem flexibel: +60% betere buigradius t.o.v. SAE 100R

Art.code	Inwendig MM*	Inwendig Inch*	Uitwendig MM*	Buigradius MM	WD BAR	BD BAR
SH124EVO	19	3/4"	30,6	120	420	1680
SH164EVO	25	1"	38,0	150	380	1520
SH204EVO	32	1.1/4"	44,0	210	350	1400
SH244EVO	38	1.1/2"	50,6	250	290	1160
SH324EVO	51	2"	64,7	318	280	1120

\* Opgegeven maten zijn onderhevig aan toleranties.

### alfabiotech EVOLUTION

- ▲ Specially designed for top performance and compatibility with biodegradable hydraulic oils
- ▲ Extreme flexibility: up to 60% better bend radius compared to SAE 100R
- ▲ Compact design & extremely flexible construction
- ▲ Minetuff cover for top abrasion & ozone resistance
- ▲ MSHA-approved fire resistant cover

BEND RADIUS  
Standard ISO 18752  
and SAE 100R

BEND RADIUS REDUCED UP TO 60%