





MARKING: 6 orange stripes, axially applied, on black cover "Continental EURO TRIX" DN 13 PN 15 BAR / 218 PSI Made in Germany"

APPLICATIONS

Agricultural sector, Construction industry, Fleets, General industry, Industry, Landscaping and gardening, Mining industry, Municipal enterprises, Over- and underground workings, Workshops

FLOW MEDIUM

Cooling water, Water

DESCRIPTION

Inner lining: EPDM, black, non-porous, smooth

Reinforcements:Synthetic fibresCover:EPDM, black, smoothWorking pressure up to: 15 bar / 218 psi

Temperature range: from -20 °C / -4 °F up to +100 °C / +212 °F

TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/2	13	3.5	20	40	15	218	45	653	50	265
5/8	16	3.8	23.6	40	15	218	45	653	65	360
3/4	19	4	27	40	15	218	45	653	70	435
1	25	4.5	34	40	15	218	45	653	120	580

Temperature resistance applies only to materials used / All technical data apply at room temperature